

N3922-24A-2

AC TO AC POWER SUPPLY

Infinova[®]



FEATURES

- Smart buildings
- Security and surveillance
- Intelligent transportation system
- Highway surveillance system

TECHNICAL SPECIFICATIONS

Input		Leakage Current	
AC Input Voltage	230V AC		N/A
AC Input Voltage range	100V TO 250V AC	Mechanical	
AC Input frequency	47Hz TO 60Hz	Dimensions	L= 115mm W= 81mm H= 70mm
Output		Weight	2.5 Kgs
Normal DC O/P Voltage	27VAC	I/P plug Type	MKDC equivalent type 3 Pin Connector with 130-145 cm. cable length.
Output Current	3A	O/P plug Type	MKDC equivalent type 3 Pin Cable with 50-65 cm. Cable length.
Output Power	60W	O/P Power Indication	LED
Short Circuit Protection	Optional	Short Circuit Protection	N/A
Environment		Certifications and Approval	
Operating Temperature	+85°C	Product Certifications	CE, FCC
Operating Humidity	N/A		
Isolation	1.5KV BETWEEN PRIMARY AND SECONDARY		

ORDERING INFORMATION

N3922-24A-2 AC to AC Power Supply, Plug-In, 230VAC, Output 24VAC, 3A