

# N3922-75P-2

POE POWER SUPPLY

**Infinova**<sup>®</sup>



## FEATURES

- Smart buildings
- Security and surveillance
- Intelligent transportation system
- Highway surveillance system

# TECHNICAL SPECIFICATIONS

<b>Input</b>	
AC Input Voltage	230V AC
AC Input Voltage range	100-240VAC 1.5A
AC Input frequency	50Hz TO 60Hz
<b>Output</b>	
Normal DC O/P Voltage	55VDC
Output Current	1.3 A
Output Power	75W
Power Pins	4/5(+), 7/8(-) and 3/6(+),1/2(-)
Data Speed	10/100/1000Mbps
<b>Environment</b>	
Operating Temperature	0°C + 60°C
Storage Temperature	-20°C + 70°C
Operating Humidity	20%-95% non-condensation

<b>Safety Precautions</b>	
Isolation	1.5KV BETWEEN PRIMARY AND SECONDARY
Line-Earth	1.2/50us (8/20us): 2KV
Line-Line	1.2/50us (8/20us): 1KV
<b>Mechanical</b>	
Dimensions	193mm X 85mm X 41mm
Case	Plastic
Color	Black
Weight	415 g
Mounting Arrangement	Wall Mount
Power Indicator	Green
PoE Load Indicator	Green

# ORDERING INFORMATION

**N3922-75P-2** Smart POE Injector, 100VAC-240VAC input, 75W output