

# V1405-11SHB-IR SERIES

INDOOR/ OUTDOOR IR CAMERA HOUSING

**Infinova®**



## FEATURES

- Smart uniform irradiation solution improves image quality & monitoring effect
- Leading IR technology provides high efficiency and long-life span of LED
- Accurate constant circuit drive develops excellent performance of product
- Power and day/night switch manually controlled
- Fill light for night vision camera
- Indoor/outdoor use, all-weather use.
- High integrated solution for easy installation and saving cost

Side opening aluminium housing V1405-11SHB-IR have been designed and manufactured to protect cameras against water and dust present in the atmosphere. The housings have been produced using highest quality aluminium materials.

# TECHNICAL SPECIFICATIONS

<b>Electrical</b>		Packing Dimension	482*225*170mm
Input Voltage	24VAC / 24VDC	Bracket (options)	Material: Aluminium Alloy
Output Voltage	DC12V 1000mA		Size: 83*123.9*304mm
Power Consumption	20W (adjustable)	Unit Weight	N.W/ G.W: 0.45KG/0.6KG
Quantity of LED	10PCS 2W High Power IR LED	Shipping Weight	7.27 lbs. (3.3kg)
Wavelength	850nm	<b>Environmental</b>	
Beam Angle	15°- 60°	Cooling	Air cooling internal circulation
IR Distance	120m-50m	Blower	Included
Day/night Switch	CDS 10-20lux ±10% (adjustable)	Working Temperature	-40°C to +60°C (-50°C to +60°C with heater)
<b>Physical</b>		Storage Temperature	-40°C to +70°C
Panel	Tempered glass panel	Protection Level	IP66
Housing	Aluminium Die Casting Housing	Color	Beige
Bracket	Bottom mount bracket	<b>Certifications and Approval</b>	
		Product Certifications	CE, FCC, IK10, IP66, NEMA4x

# ORDERING INFORMATION

V1405-11SHB-IR-1	IR Camera housing, indoor/outdoor, 15° beam angle, 120m IR distance
V1405-11SHB-IR-2	IR Camera housing, indoor/outdoor, 30° beam angle, 110m IR distance
V1405-11SHB-IR-3	IR Camera housing, indoor/outdoor, 45° beam angle, 70m IR distance
V1405-11SHB-IR-4	IR Camera housing, indoor/outdoor, 60° beam angle, 50m IR distance
<b>Accessories</b>	
<b>Mount</b>	
V1573-A	Wall Mount, H/V adjustability for housing (V1405, V1405-11SHB-IR), 88.19 lbs. (40 kg) load, Cable Management

# DIMENSIONS

