

# V1405-11SHB-IR SERIES

INDOOR/ OUTDOOR IR CAMERA HOUSING

**Infinova**<sup>®</sup>



## FEATURES

- Smart uniform irradiation solution improves image quality & monitoring effect
- Leading IR technology provides high efficiency and long-life span of LED
- Accurate constant circuit drive develops excellent performance of product
- Power and day/night switch manually controlled
- Fill light for night vision camera
- Indoor/outdoor use, all-weather use.
- High integrated solution for easy installation and saving cost

Side opening aluminium housing V1405-11SHB-IR have been designed and manufactured to protect cameras against water and dust present in the atmosphere. The housings have been produced using highest quality aluminium materials.

# TECHNICAL SPECIFICATIONS

<b>Electrical</b>	
Input Voltage	24VAC / 24VDC
Output Voltage	DC12V 1000mA
Power Consumption	20W (adjustable)
Quantity of LED	10PCS 2W High Power IR LED
Wavelength	850nm
Beam Angle	15°- 60°
IR Distance	120m-50m
Day/night Switch	CDS 10-20lux ±10% (adjustable)
<b>Physical</b>	
Panel	Tempered glass panel
Housing	Aluminium Die Casting Housing
Bracket	Bottom mount bracket

Packing Dimension	482*225*170mm
Bracket (options)	Material: Aluminium Alloy Size: 83*123.9*304mm N.W/ G.W: 0.45KG/0.6KG
Unit Weight	7.27 lbs. (3.3kg)
Shipping Weight	8.48 lbs. (3.85kg)
<b>Environmental</b>	
Cooling	Air cooling internal circulation
Blower	Included
Working Temperature	-40°C to +60°C (-50°C to +60°C with heater)
Storage Temperature	-40°C to +70°C
Protection Level	IP66
Color	Beige
<b>Certifications and Approval</b>	
Product Certifications	CE, FCC, IK10, IP66, NEMA4x

# ORDERING INFORMATION

V1405-11SHB-IR1	IR Camera housing, indoor/outdoor, 15° beam angle, 120m IR distance
V1405-11SHB-IR2	IR Camera housing, indoor/outdoor, 30° beam angle, 110m IR distance
V1405-11SHB-IR3	IR Camera housing, indoor/outdoor, 45° beam angle, 70m IR distance
V1405-11SHB-IR4	IR Camera housing, indoor/outdoor, 60° beam angle, 50m IR distance
<b>Accessories</b>	
<b>Mount</b>	
V1573-A	Wall Mount, H/V adjustability for housing (V1405, V1405-11SHB-IR), 88.19 lbs. (40 kg) load, Cable Management

# DIMENSIONS

