
V3073-16J08
Network Video Recorder



- **Adopts professional high performance multi-media network processor and embedded Linux system, low power consumption and high stabilization**
- **Supports simultaneous HDMI and VGA output, with a resolution up to 4K for HDMI output and 1920×1080P for VAG output**
- **Supports H.265/H.264 video format**
- **Supports to add IP camera with one click**
- **Supports preview, recording and playback of 8.0MP IP camera**
- **Supports 128Mbps incoming and outgoing bandwidth**
- **Supports 16chnetwork video preview and recording**
- **Supports 16-channel HD video real-time decoding and synchronous playback**
- **Supports 8 SATA hard disk ports**
- **Supports ONVIF and RTSP protocol and can connect to IP cameras from lots of leading manufacturers**

The V3073-16J08 embedded HD network video recorder is an HD surveillance and storage device that integrates HD image decoding technology, network technology and storage technology, supporting mainstream brand network cameras access.

The product can be widely used in professional safety and security surveillance areas of safe city, bank, smart transportation, smart building, hospital, school, community, factory etc.


Copyright © 1993-2020 Infinova. All rights reserved. Appearance and specifications are subject to change without prior notice.

Technical specifications

System	
Operating System	Embedded Linux system
Video/Audio Input	
Incoming Bandwidth	128Mbps
Outgoing Bandwidth	128Mbps
IPC Input	16CH
Audio In	1CH, RCA (Line out, 2Vp-p, 300ohms)
Video/Audio Output	
VGA	1CH, 1920×1080, 1280×1024, 1280×720, 1024×768
HDMI	Standard 1.4a 3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768
Audio Output	1CH, RCA (Line out, 2Vpp, 300ohms)
Audio Encoding	
Audio Compression	G.711A
Audio Bit Rate	64Kbps
Video/Audio Decoding	
IP channel Resolution	Main stream up to 3264x2448 Auxiliary stream: D1
Video Decoding	H.265 (Main Profile @ Level 5.0) / H.264 (High Profile @ Level 5.1)
Audio Decoding	G.711A, G726
Synchronous Playback	Up to 16CH
Decoding Ability	16CH 1080P@30FPS

Other Function	
Bidirectional Talk	Two-way voice intercom function
Motion Detection	Zones: 396 (22*18), Sensitivity: 1~6 (level 6 is highest)
Picture Capture	Support JPEG Capture
HDD Interface	
SATA	8 SATA Interfaces
Max Capacity	8T
External Interface	
Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet interfaces
USB Interface	3 USB2.0 Interfaces
HDMI interface	HDMI1, HDMI2
Alarm In	16CH
Alarm Out	4CH NO/NC
RS-232	1 RS-232 interface
RS-485	1 RS-485 interface
Structure	
Dimensions	520x520x215mm
Size	2U, 441x448x88mm
Weight	7Kg (without HDD)
Installation	Desktop Installation, Rack mounting Installation
General	
Power Supply	AC 110V~220V ± 10% 47Hz～63Hz
Working Temperature	0°C~+55°C
Working Humidity	10%~95%
Consumption	20W (without HDD, without POE)
Certificate	CE, FCC

Panel view



Copyright © 1993-2020 Infinova. All rights reserved. Appearance and specifications are subject to change without prior notice.


Ordering information

V3073-16J08	Network video recorder, 16ch video inputs, support 8HDD slots, w/o HDDs

V3091 series SATA HDD—surveillance level

V3091-2000-S3	2TB, 3.5 inch, 5900rpm, 64MB cache, SATA
V3091-3000-S3	3TB, 3.5 inch, 5900rpm, 64MB cache, SATA
V3091-4000-S	4TB, 3.5 inch, 5900rpm, 64MB cache, SATA
V3091-6000-S5	6TB, 3.5 inch, 5900rpm, 256MB cache, SATA

Dimensions (unit: mm)



Copyright © 1993-2020 Infinova. All rights reserved. Appearance and specifications are subject to change without prior notice.