

V1405 SERIES

INDOOR/ OUTDOOR MINI CAMERA HOUSING

Infinova[®]



FEATURES

- Spring loaded top cover
- Rear lock-in latch connection
- Die-cast aluminium
- Indoor/outdoor installations
- IP66 standard
- Easy installation and maintenance
- Cable clamps and installation holes on the housing bottom

The V1405 series are affordable die-cast aluminium camera housings for both indoor and outdoor installations. The V1405 housings accommodate CCD cameras with fixed or vari-focal lens. The top cover is spring loaded to facilitate installation. There are two adjustable weatherproof cable clamps on the bottom for easy installation of video and power cables. A rear lock-in latch secures the spring-loaded cover for added security. The V1405 have a set of optional accessories which can be installed at the factory, including sunshield and heater. The input voltage is available in 24 VAC. The V1405 are compatible with small to medium size cameras, and can be installed on either fixed mounts or pan/tilts.

TECHNICAL SPECIFICATIONS

Electrical	
Input Voltage	24 VAC, 50/60 Hz
Power Consumption	25 W
Physical	
Camera Mounting	Multiple installation holes available on the camera supporting board, which is installed on the two narrow slots in the bottom groove for easy disassembly.
Internal Usable Dimensions (L×W×H)	9.84"×3.54"×2.85" (250 mm×90 mm×72.5 mm)
Window Thickness	0.16" (4 mm)
Window Dimensions (W×H)	2.64"×2.24" (67 mm×57 mm)
Cable Input	Two compressed cable glands with the max diameter of 0.48" (12 mm) available on the bottom
Lock-in Latch	Stainless steel; padlock (not included) can also be used to secure

Construction	Die-cast aluminium
Box Dimensions (L×W×H)	19.49"×6.50"×6.26" (495 mm×165 mm×159 mm)
Unit Weight	5.73 lbs. (2.6 kg)
Shipping Weight	10: 5.95 lbs. (2.7 kg)
Environmental	
Auto Controlled Temperature	Heater: Turns on at 46°F ± 9°F (8°C ± 5°C); Turns off at 68°F ± 9°F (20°C ± 5°C)
Environment	Indoor/outdoor
Operating Temperature	23°F ~140°F (-5°C ~ 60°C); -13°F ~140°F (-25°C ~ 60°C) (w/ heater)
Certifications and Approval	
Product Certifications	IP66, IK10, CE

ORDERING INFORMATION

V1405-10	Camera Housing, Indoor/outdoor, 10 inch internal
V1405-10S	Camera Housing, Indoor/outdoor, 10 inch internal, w/ sun shield
V1405-10SHB	Camera Housing, Indoor/outdoor, 10 inch internal, w/ sun shield, heater & blower, 24VAC
Accessories	
Mount	
V1571-W	Wall Mount, H/V adjustable for housing (V1405), 33.07 lbs (15 kg) load
V1573	Mount Adapter, H/V adjustability for housing (V1405, V1406, V1407), 44.09 lbs (20 kg) load